



Padded jacket in 'clean' look for business and leisure

Smooth outside, inside in stitching, with DuPont™ Sorona® padding (renewable, organic raw material)
 Wind- and waterproof fabric (5,000 mm water column)
 Breathable and permeable to water vapour (1,500 g/m²/24h)
 Stand-up collar
 Adjustable, detachable hood
 Full-length concealed front zip
 2 front pockets, 2 sewn-on breast pockets, 1 zipped inner pocket
 Elastic inner sleeve bands
 Zip for decoration at the back
 YKK-zips
 JN1157 : Elastic inner cord for waist adjustmen

Fabric:	Outer fabric: 100% polyester Lining: 100% polyamide Padding: 100% polyester
Country of origin:	Myanmar (Burma)
Customs tariff number	62019300

Care instructions



Partner article



Ladies' Business Jacket
 Art-Nr.: JN1157

Available colours

	S	M	L	XL	XXL	3XL
Weight in g	726g	742g	776g	812g	839g	876g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/25	1/25	1/25	1/25	1/25	1/25
measurements in cm	S	M	L	XL	XXL	3XL
1/2 chest:	55,00 cm	58,00 cm	61,00 cm	64,00 cm	67,00 cm	70,00 cm
length from shoulder:	72,00 cm	74,00 cm	76,00 cm	78,00 cm	79,50 cm	81,00 cm
sleeve length:	68,00 cm	69,00 cm	70,00 cm	71,00 cm	72,00 cm	73,00 cm

Available colours

■ black (blackC)
 ■ navy (296C)

■ black-melange (447C)

■ graphite (432C)



DuPont™ Sorona®

Sorona® renewably sourced fiber delivers superior performance benefits to today's fashions. Fabrics that use Sorona® are very soft, very strong and dry quickly. Sorona® helps fabrics stretch comfortably and retain their shape. And, it is made with plant-based ingredients. DuPont™ Sorona®. Designed for Performance. Derived from Nature.



Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m² within 24 hours. The higher this figure, the more breathable the textile is.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.